

uPVC ACOUSTIC DATASHEET

Ambiance Inline Window Systems



uPVC Acoustic Datasheet

Glazing Spec	RW (C, CTR) Glazing (DB)	RW (C, CTR) Window (DB)	Report Number
4/16/4 T AR thermal spacer + argon)	31(-2,-5)	34(-2,-5)	LA-01228:b/2010
6/16/4 T Ar	34(-1,-5)	38(-2,-6)	
6/16/6 T Ar	35(-3,-7)	37(-2,-4)	
44.2/16/4 T Ar	37(-1,-5)	41(-2,-5)	
44.2/16/6 T Ar	39(-4,-8)	41(-2,-5)	
33.1f.acoustic./16/6 T Ar	40(-2,-6)	43(-2,-6)	
44.2f.acoustic./16/6 T Ar	41(-2,-6)	43(-2,-5)	
8 VSG TF/16/6	42	42(-2,-6)	16129751/Z02 R1
9 VSG Si/16/6	41	42(-2,-5)	16129751/Z01 R1
9 VSG Si/16/10	45	44(-1,-2)	16129751/Z03 R1
13 VSG Si/19/9 VSG Si	48	45(-1,-3)	16129751/Z05 R1
4/16/4		33	010424.S24
6/16/4		37	010424.S21
10/16/4		39	001127.P14