

STÄRKE

a window to a better world

QUICK REFERENCE SELECTION GUIDE

Ambiance Inline Window Systems



1 Choose your frame & door

Entry Level

- White 70mm
- Black 70mm
- Vario-slide door

High Air-tightness

- White 70mm
- Black 70mm
- Smart-slide door

Very high performance flush sill

- White 70mm
- Black 70mm
- Lift & slide door

2 Choose your glazing

Pane 1

- Base Low-E**
Low-E, Argon Gas, Warm Edge Spacer. U1.7, G0.74
- Energy efficient, let heat in (Lightbridge)**
High Performance Low-E, Argon Gas, Warm Edge Spacer. U1.1, G0.62
- Energy efficient, block heat out (performatech)**
High Performance Low-E, Argon Gas, Warm Edge Spacer. U1.1, G0.35

Pane 2

- Block UV (lamine)**
Reduces 99% of UV rays, the primary cause of furniture fading
- Block sound (lamine)**
Increase STC (decibels reduces) from 30 to 35, or 37 with Hush
- Tint (colours)**
Grey, Green. No material affect on thermal performance

3 Finalise configurations

(select all that apply)

Windows

- Traditional
- Tilt & Turn
- Sliding

Doors

- French
- Sliding/Stacking
- Invisifold
- Entry door

4 Final confirmations

Interior Reveal / Architrave

- AMBIANCE™ Integrated reveal
- Traditional Timber (not supplied)

H1/AS1 Compliance Method

- Stärke Energy Modelling Services
- Other

Cladding Specification

Depth (mm)
35/45/60/65/85

Depth (mm)
35/45/60/65/85

Type 1:

Type 3:

Type 2:

Type 4: